MOTOR UNIT MM-30V

400W motor block. Variable speed.





falling.

✓ Approved by NSF: guaranteed safety and hygiene.

NCLUDES

√ Variable speed motor block

SPECIFICATIONS

Total loading: 400 W

Motor speed: 1500 - 12000 rpm Blade guard diameter: -- mm

Net weight: 2.46 Kg Noise level (1m.): <80 dB(A)

AVAILABLE MODELS

3030667 Motor unit MM-30V 230/50-60/1

* Ask for special versions availability

ACCESSORIES

☐ Mixer arms MA-30

☐ Whisk BA-30

SALES DESCRIPTION

Variable speed motor block.

Designed for continuous use.

Professional performance

- √ Vario-speed: variable speed.
- ✓ Designed to work in recipients of up to 60 litres.
- √ 3 mixer arm lengths available.
- √ Whisk available.

Maximum comfort for the user

- √ Compact design: logical and manageable size.
- ✓ Ergo-design & bi-mat-grip: external casing made in two materials for an ergonomic hold. Anti-slip grip. Optimum inclination of handle, minimising fatigue.
- Click-on-arm: detachable arm with fast and secure closure.
- ✓ Intuitive use: very simple operation. Warning light when the machine is connected to the mains.
- √ Possiblity of continuous operation.

Built to last

- Professional performance: capable of carrying out prolonged work without the casing overheating.
- √ Life-plus: equipped with a motor which has passed all of the most demanding usage tests.
- √ Studied geometry: casing designed to avoid rolling and





20720 Azkoitia, Spain





Project	Date
Item	Qty
Approved	