VACUUM PACKING MACHINE SE-420 230/50-60/1

Tabletop model. 20 m³/h. 420 mm.

P/N 1140638



SALES DESCRIPTION

420 mm. sealing bar.

20 m³/h Busch vacuum pump.

Vacuum controlled by sensor.

- √ Powered by Busch.
- √ Vacuum controlled by sensor.
- √ Vacuum PLUS.
- ✓ Digital keyboard.
- ✓ Control panel equipped with display indicating the exact vacuum percentage.
- √ "Pause" button to marinate food.
- ✓ Safe liquid packing thanks to sensor control.
- ✓ Double seal.
- √ Cordless sealing bar.
- √ Bag-sealing programme.
- ✓ Pulse-controlled decompression.
- √ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid of highly durable polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- √ Working hours counter for oil changes.
- Safety system with protection against vacuum failure.





INCLUDES

- √ Sensor Controls
- √ Up to 10 seconds of extra vacuum pull
- Soft air function
- √ Dry oil cycle
- √ BUSCH pump
- NSF Approved
- ✓ Clear methacrylate lid
- √ Filling plate

SPECIFICATIONS

Pump capacity: 20 m3/h

Bar length: 420 mm Total loading: 750 W

Vacuum pressure (maximum): 2 mbar

Electrical supply: 230 V / 50-60 Hz / 1 ~ (5.5 A)

Internal dimensions

- √ Width: 430 mm
- ✓ Depth: 415 mm
- √ Height: 180 mm

External dimensions (WxDxH)

- √ Width: 484 mm
- √ Depth: 529 mm
- √ Height: 448 mm

Net weight: 56.7 Kg

Noise level (1m.): -- dB(A)

Background noise: 32 dB(A)

Crated dimensions

600 x 600 x 610 mm

Gross weight: 62 Kg.

ACCESSORIES

- Bag cutting kits
- □ Filling plates
- ☐ Liquid insert plates
- Vac-norm external vacuum
- Vac-norm containers
- □ Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing machines





phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty

Approved