



VACUUM PACKING MACHINE SE-520 230/50-60/1

Tabletop model. 20m³/h. 420+420 mm.



P/N 1140642



SALES DESCRIPTION

Two sealing bars (420+420 mm.)

20 m³/h Busch vacuum pump.

Vacuum controlled by sensor.

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ Digital keyboard.
- ✓ Control panel equipped with display indicating the exact vacuum percentage.
- ✓ "Pause" button to marinate food.
- ✓ Safe liquid packing thanks to sensor control.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Bag-sealing programme.
- ✓ Pulse-controlled decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Long-shaped chamber.
- ✓ Damped transparent lid of highly durable polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.



INCLUDES

- ✓ Sensor Controls
- ✓ Up to 10 seconds of extra vacuum pull
- ✓ Soft air function
- ✓ Dry oil cycle
- ✓ BUSCH pump
- ✓ NSF Approved
- ✓ Clear methacrylate lid
- ✓ Filling plate

SPECIFICATIONS

Pump capacity: 20 m³/h

Bar length: 420 mm

Total loading: 750 W

Vacuum pressure (maximum): 2 mbar

Electrical supply: 230 V / 50-60 Hz / 1 ~ (5.5 A)

Internal dimensions

- ✓ Width: 560 mm
- ✓ Depth: 430 mm
- ✓ Height: 183 mm

External dimensions (WxDxH)

- ✓ Width: 625 mm
 - ✓ Depth: 537 mm
 - ✓ Height: 513 mm
- Net weight: 81.1 Kg
- Noise level (1m.): 75 dB(A)
- Background noise: 32 dB(A)

Crated dimensions

604 x 777 x 650 mm

Gross weight: 84 Kg.

ACCESSORIES

- ☐ Bag cutting kits
- ☐ Filling plates
- ☐ Liquid insert plates
- ☐ Vac-norm external vacuum kits
- ☐ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing machines

sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

product sheet
updated 02/08/2019

FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR" LINE