



VACUUM PACKING MACHINE SU-604 230-400/50/3N

Floorstanding unit. 40 m³/h. 413+656 mm.



P/N 1140811

FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE



FEATURES AND BENEFITS

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- ✓ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.
- ✓ NSF-listed.

SALES DESCRIPTION

Two sealing bars (413+656 mm.)
40 m³/h Busch vacuum pump.
Vacuum controlled by sensor.

INCLUDES

- ✓ BUSCH pump.
- ✓ Sensor Controls.
- ✓ 25 programmable settings.
- ✓ Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ "PAUSE" function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF Approved.
- ✓ Filling plate.

ACCESSORIES

- ☐ Bag cutting kits
- ☐ Filling plates
- ☐ Liquid insert plates
- ☐ Vac-norm external vacuum kits
- ☐ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- ☐ CG2 Desktop printer for SU vacuum packing machines *
- ☐ Thermal labels for CG2 printer
- ☐ RB Desktop printer for SU vacuum packing machines *
- ☐ Thermal transfer labels for printer



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

product sheet
updated 22/03/2019



VACUUM PACKING MACHINE SU-604 230-400/50/3N

Floorstanding unit. 40 m³/h. 413+656 mm.



P/N 1140811

SPECIFICATIONS

Pump capacity: 40 m³/h

Bar length: 413 mm + 656 mm

Total loading: 1100 W

Vacuum pressure (maximum): 0.5 mbar

Electrical supply: 400 V-230 V / 50 Hz / 3N
~ (5.9 A)

Internal dimensions

✓ Width: 672 mm

✓ Depth: 481 mm

✓ Height: 200 mm

External dimensions (WxDxH)

✓ Width: 740 mm

✓ Depth: 566 mm

✓ Height: 997 mm

Net weight: 145 Kg


Noise level (1m.): 75 dB(A)

Background noise: 32 dB(A)

Crated dimensions

670 x 830 x 1200 mm

Gross weight: 170.5 Kg.



FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE

sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

product sheet
updated 22/03/2019